arXiv:1510.08892v1 [cs.DS] 29 Oct 2015

A Randomized Algorithm for Long Directed Cycle[☆]

Meirav Zehavi[*]

Department of Computer Science, Technion IIT, Haifa 32000, Israel

Abstract

Given a directed graph G and a parameter k, the Long Directed Cycle (LDC) problem asks whether G contains a simple cycle on at least k vertices, while the k-Path problems asks whether G contains a simple path on exactly k vertices. Given a deterministic (randomized) algorithm for k-Path as a black box, which runs in time $t(G,k)$, we prove that LDC can be solved in deterministic time $O^*(\max\{t(G,2k),4^{k+o(k)}\})$ (randomized time $O^*(\max\{t(G,2k),4^k\})$). In particular, we get that LDC can be solved in randomized time $O^*(4^k)$.

Keywords: algorithms, parameterized complexity, long directed cycle, k-path

1. Introduction

We study the Long Directed Cycle (LDC) problem. Given a directed graph $G=(V,E)$ and a parameter k, it asks whether G contains a simple cycle on *at least* k vertices. At first glance, this problem seems quite different from the well-known k-Path problem, which asks whether G contains a simple path on *exactly* k vertices: while k-Path seeks a solution whose size is exactly k, the size of a solution to LDC can be as large as $|V|$. Indeed, in the context of LDC, Fomin *et al.* [1] noted that "color-coding, and other techniques applicable to k-Path do not seem to work here."

In this paper, we show that an algorithm for k-Path can be used as a *black box* to solve LDC efficiently. More precisely, suppose that we are given a deterministic (randomized) algorithm ALG that uses $t(G,k)$ time and $s(G,k)$ space, and decides whether G contains a simple path on *exactly* k vertices directed from v to u for some given vertices $v,u\in V$.[1] Then, we prove that LDC can be solved in deterministic time $O^*(\max\{t(G,2k),4^{k+o(k)}\})$ and $O^*(\max\{s(G,k),4^{k+o(k)}\})$ space (if ALG is deterministic), or in randomized time $O^*(\max\{t(G,2k),4^k\})$ and $O^*(s(G,k))$ space (if ALG is randomized).[2] Somewhat surprisingly, we

[☆] *Abbreviations*: Long Directed Cycle (LDC).

[*] Corresponding author.

Email address: meizeh@cs.technion.ac.il (Meirav Zehavi)

[1] Known algorithms for k-Path handle the condition relating to the vertices v and u.

[2] The O^* notation hides factors polynomial in the input size.

show that cases that cannot be efficiently handled by calling an algorithm for k-PATH, can be efficiently handled by merely using a combination of a simple partitioning step and BFS.

The first parameterized algorithm for LDC, due to Gabow and Nie [2], runs in time $O^*(k^{O(k)})$. Then, Fomin *et al.* [1] gave a deterministic parameterized algorithm for LDC that runs in time $O^*(8^{k+o(k)})$ using exponential-space. Recently, Fomin *et al.* [3] and the paper [4] modified the algorithm in [1] to run in deterministic time $O^*(6.75^{k+o(k)})$ using exponential-space. It is known that k-PATH can be solved in randomized time $O^*(2^k)$ and polynomial-space [5], and deterministic time $O^*(2.59606^k)$ and exponential-space [6]. Thus, we immediately obtain that LDC can be solved in randomized time $O^*(4^k)$ and polynomial-space, and deterministic time $O^*(6.73953^k)$ and exponential-space.

In the following sections, given a graph $G = (V, E)$ and a set $U \subseteq V$, we let $G[U]$ denote the subgraph of G induced by U.

2. Finding Large Solutions in Polynomial-Time

We say that an instance (G, k) of LDC *seems difficult* if G does not contain a directed cycle on ℓ vertices for any $\ell \in \{k, k+1, \ldots, 2k\}$. Roughly speaking, given such an instance, we are forced to determine whether G contains a *large* solution. This case, as noted in [2] and [1], seems to be the core of difficulty of LDC. We show, somewhat surprisingly, that under certain conditions, this case can be solved in polynomial-time. More precisely, this section proves the correctness of the following lemma.

Lemma 1. *Let (G, k) be instance of* LDC*, and let (L, R) be a partition of V. Then, there is a deterministic polynomial-time algorithm,* PolyAlg*, which satisfies the following conditions.*

- *If (G, k) seems difficult, and G contains a simple cycle $v_1 \to v_2 \to \ldots \to v_t \to v_1$ such that $t > 2k$, $v_1, v_2, \ldots, v_k \in L$ and $v_{k+1}, v_{k+2}, \ldots, v_{2k} \in R$,* PolyAlg *accepts.*
- *If G does not contain a simple cycle on at least k vertices,* PolyAlg *rejects.*

PROOF. The pseudocode of PolyAlg is given in Algorithm 1. Clearly, if the algorithm accepts, there exist two distinct vertices v and u such that G contains two simple internally vertex disjoint paths, $P = (V_P, E_P)$ (from v to u) and $P' = (V'_P, E'_P)$ (from u to v), where $|V_P| = k$. In this case, G contains a simple cycle, which consists of these paths, on at least k vertices. Thus, the second item is correct.

Now, we turn to prove the first item. To this end, suppose that the condition of this item is true. Then, we can let $C = v_1 \to v_2 \to \ldots \to v_t \to v_1$ be a simple cycle in G such that $t > 2k$, $v_1, v_2, \ldots, v_k \in L$ and $v_{k+1}, v_{k+2}, \ldots, v_{2k} \in R$, *which minimizes* t. We need the following observations.

Observation 1. *The number of vertices on the shortest path from v_1 to v_k in $G[L]$ is exactly k.*

Algorithm 1 PolyAlg$(G = (V, E), k, L, R)$

for all $v \in L$ and $u \in L \setminus \{v\}$ **do**
  Use BFS to find a simple path $P = (V_P, E_P)$ from v to u in $G[L]$ that minimizes $|V_P|$.
  if $|V_P| \neq k$ or the path P does not exist **then**
    Skip the rest of this iteration.
  end if
  Use BFS to find a simple path $P' = (V'_P, E'_P)$ from u to v in $G[V \setminus (V_P \setminus \{v, u\})]$ that minimizes $|V'_P|$.
  if the path P' exists **then**
    Accept.
  end if
end for
Reject.

PROOF. The existence of C implies that we can let $P = (V_P, E_P)$ denote a path from v_1 to v_k in $G[L]$ that minimizes $|V_P|$, and that we can assume that $|V_P| \leq k$. We furhter denote $P = u_1 \to u_2 \to \ldots \to u_{|V_P|}$, where $u_1 = v_1$ and $u_{|V_P|} = v_k$. It remains to show that $|V_P| = k$. Suppose, by way of contradiction, that $|V_P| < k$. Let v_i be the first vertex on the path $v_{k+1} \to v_{k+2} \to \ldots \to v_t \to v_1$ that belongs to V_P. Then, we can define a simple cycle C' in G as follows.

- If $i = 1$: $C' = v_{k+1} \to v_{k+2} \to \ldots \to v_t \to (v_1 = u_1) \to u_2 \to \ldots \to (u_{|V_P|} = v_k) \to v_{k+1}$.
- Else: Let j be the index such that $v_i = u_j$. Then, $C' = v_{k+1} \to v_{k+2} \to \ldots \to v_{i-1} \to (v_i = u_j) \to u_{j+1} \to \ldots \to (u_{|V_P|} = v_k) \to v_{k+1}$.

Clearly, the number of vertices of C' is smaller than t. Therefore, by the choice of C and since (G, k) is a seemingly difficult instance of LDC, we have that C' is a cycle on less than k vertices. However, since $V_P \subseteq L$ and $v_{k+1}, v_{k+2}, \ldots, v_{2k} \in R$ (where $R = V \setminus L$), we have that $2k < i$. This implies that C' is a cycle on at least k vertices, and thus we have reached a contradiction. □

Observation 2. *Let $P = (V_P, E_P)$ be a simple path from v_1 to v_k in $G[L]$ such that $|V_P| = k$. Then, $G[V \setminus (V_P \setminus \{v_1, v_k\})]$ contains a path from v_k to v_1.*

PROOF. Denote $P = u_1 \to u_2 \to \ldots \to u_k$, where $u_1 = v_1$ and $u_k = v_k$. If $V_P \cap \{v_{k+1}, v_{k+2}, \ldots, v_t\} = \emptyset$, then the claim is clearly true, since then $v_k \to v_{k+1} \to \ldots \to v_t \to v_1$ is a path in $G[V \setminus (V_P \setminus \{v_1, v_k\})]$. Suppose, by way of contradiction, that $V_P \cap \{v_{k+1}, v_{k+2}, \ldots, v_t\} \neq \emptyset$. Then, we can let v_i be the first vertex on the path $v_{k+1} \to v_{k+2} \to \ldots \to v_t$ that belongs to V_P. Let j be the index such that $v_i = u_j$. We have that $C' = v_{k+1} \to v_{k+2} \to \ldots \to v_{i-1} \to (v_i = u_j) \to u_{j+1} \to \ldots \to (u_k = v_k) \to v_{k+1}$ is a simple cycle in G. Now, we reach a contradiction in the same manner as it is reached in the last paragraph of the proof of the previous observation. □

Consider the iteration of Step 1 that corresponds to $v = v_1$ and $u = v_k$. The first observation implies that the condition of Step 3 is false. Next, the second observation implies that the condition of Step 6 is true, and therefore PolyAlg accepts. □

3. Computing the Sets L and R

In this section we observe that the computation of the sets L and R can merely rely on a simple partitioning step. To this end, we need the following definition and known result.

Definition 1. *Let $\mathcal{F}$ be a set of functions $f : \{1, 2, \ldots, n\} \to \{0, 1\}$. We say that $\mathcal{F}$ is an (n, t)-universal set if, for every subset $I \subseteq \{1, 2, \ldots, n\}$ of size t and a function $f' : I \to \{0, 1\}$, there is a function $f \in \mathcal{F}$ such that, for all $i \in I$, $f(i) = f'(i)$.*

Lemma 2 ([7]). *There is a deterministic algorithm that given a pair of integers (n, t), computes in $O^*(2^{t+o(t)})$ time and space an (n, t)-universal set $\mathcal{F} \subseteq 2^{\{1,2,\ldots,n\}}$ of size $O^*(2^{t+o(t)})$.*

Now, we turn to prove the following simple observations.

Observation 3. *Let $(G = (V, E), k)$ be a instance of* LDC*. Then, there is a deterministic algorithm,* DetLRAlg*, that uses $O^*(4^{k+o(k)})$ time and space, and returns a set $S = \{(L, R) : L \subseteq V, R = V \setminus L\}$ of size $O^*(4^{k+o(k)})$ such that the following condition is satisfied.*

- *For any simple cycle $v_1 \to v_2 \to \ldots \to v_t \to v_1$ of G such that $t \geq 2k$, there exists $(L, R) \in S$ such that $v_1, v_2, \ldots, v_k \in L$ and $v_{k+1}, v_{k+2}, \ldots, v_{2k} \in R$.*

Proof. DetLRAlg arbitrarily orders V, and denotes $V = \{v_1, v_2, \ldots, v_{|V|}\}$ accordingly. It obtains an $(|V|, 2k)$-universal set $\mathcal{F}$ by relying on Lemma 2. Then, it defines $L_f = \{v_i \in V : f(i) = 0\}$ and $R_f = V \setminus L$ for each $f \in \mathcal{F}$, and lets $S = \{(L_f, R_f) : f \in \mathcal{F}\}$. The correctness and running time of the algorithm follow immediately from Definition 1 and Lemma 2. □

Observation 4. *Let $(G = (V, E), k)$ be a instance of* LDC*. Then, there is a randomized algorithm,* RandLRAlg*, with polynomial time and space complexities, that returns a partition (L, R) of V. Moreover, if* RandLRAlg *is called $c \cdot 4^k$ times for some $c \geq 1$, and G contains a simple cycle $v_1 \to v_2 \to \ldots \to v_t \to v_1$ such that $t \geq 2k$, then with probability at least $(1 - e^{-c})$, at least one of the calls returns a pair (L, R) such that $v_1, v_2, \ldots, v_k \in L$ and $v_{k+1}, v_{k+2}, \ldots, v_{2k} \in R$.*

Proof. RandLRAlg initializes L to be an empty set, and R to be V. For each $v \in V$, with probability $\frac{1}{2}$ it removes v from R and inserts v into L. Then, it returns the resulting pair (L, R), which is clearly a partition of V.

To prove the correctness of RandLRAlg, suppose that G contains a simple cycle $v_1 \to v_2 \to \ldots \to v_t \to v_1$ such that $t \geq 2k$. Then, the probability that

$v_1, v_2, \ldots, v_k \in L$ and $v_{k+1}, v_{k+2}, \ldots, v_{2k} \in R$ is $(\frac{1}{2})^{2k} = \frac{1}{4^k}$. Now, if RandLRAlg is called $c \cdot 4^k$ times, the probability that none of the calls returns a pair (L, R) such that $v_1, v_2, \ldots, v_k \in L$ and $v_{k+1}, v_{k+2}, \ldots, v_{2k} \in R$ is $(1 - \frac{1}{4^k})^{c \cdot 4^k} \leq e^{-c}$.□

4. Solving the LDC Problem

We are now ready to solve LDC. The input for our algorithm, LDCALg, consists of an instance (G, k) of LDC, an algorithm ALG for k-PATH, and an argument $X \in \{det, rand\}$ that specifies whether ALG is deterministic or randomized. LDCAlg first determines whether G contains a simple cycle on ℓ vertices, for any $\ell \in \{k, k+1, \ldots, 2k\}$ by calling ALG. If no such cycle is found, LDCAlg examines enough pairs (L, R), computed using the algorithm in Observation 3 or 4, and accepts *iff* PolyAlg accepts one of the resulting inputs (G, k, L, R). The pseudocode of LDCALg is given in Algorithm 2.

Algorithm 2 LDCAlg$(G = (V, E), k, ALG, X)$

```
1: for ℓ = k, k+1, ..., 2k do
2:    for all (u, v) ∈ E do
3:       Use ALG to determine whether G contains a simple path on exactly ℓ
         vertices directed from v to u. If the answer is positive, accept.
4:    end for
5: end for
6: if X = det then
7:    Let S be the set returned by DetLRAlg (see Observation 3), ordered ar-
      bitrarily. Moreover, let x = |S|, and let PartitionAlg be a procedure that
      when called at the i^st time, returns the i^st pair (L, R) in S.
8: else
9:    Let x = 10 · 4^k, and let PartitionAlg be RandLRAlg (see Observation 4).
10: end if
11: for i = 1, 2, ..., x do
12:    Call PartitionAlg to obtain a pair (L, R).
13:    If PolyAlg(G, k, L, R) accepts: Accept.
14: end for
15: Reject.
```

Theorem 1. *Let ALG be an algorithm that uses $t(G, k)$ time and $s(G, k)$ space, and decides whether G contains a simple path on* exactly *k vertices directed from v to u for some given vertices $v, u \in V$. Then,* LDCAlg *solves* LDC *in deterministic time $O^*(\max\{t(G, 2k), 4^{k+o(k)}\})$ and $O^*(\max\{s(G, k), 4^{k+o(k)}\})$ space (if ALG is deterministic), or in randomized time $O^*(\max\{t(G, 2k), 4^k\})$ and $O^*(s(G, k))$ space (if ALG is randomized).*

PROOF. First, observe that the time and space complexities of LDCAlg directly follow from the pseudocode, Lemma 1 and Observations 3 and 4. Moreover, by

Lemma 1 and the correctness of ALG, if LDCAlg accepts, it is clearly correct (if $X = rand$, we mean that LDCAlg accepts with high probability).[3]

Now, to complete the proof, suppose that (G, k) is a yes-instance. If G contains a simple cycle on ℓ vertices for some $\ell \in \{k, k+1, \ldots, 2k\}$, then one of the calls to ALG accepts, and therefore LDCAlg accepts (if $X = rand$, we mean that LDCAlg accepts with high probability). Thus, we can next assume that (G, k) seems difficult, and let $C = v_1 \to v_2 \to \ldots \to v_t \to v_1$ denote a simple cycle in G, where $t > 2k$. By Observations 3 and 4, there is a call to PartitionAlg where it returns a pair (L, R) such that $v_1, v_2 \ldots, v_k \in L$ and $v_{k+1}, v_{k+2}, \ldots, v_{2k} \in R$ (in case $X = rand$, we mean that there is such a call with high probability). Then, by Lemma 1, PolyAlg accepts, and therefore LDCAlg accepts. □

References

[1] F. V. Fomin, D. Lokshtanov, S. Saurabh, Efficient computation of representative sets with applications in parameterized and exact agorithms, in: SODA (see also arXiv:1304.4626), 2014, pp. 142–151.

[2] H. N. Gabow, S. Nie, Finding a low directed cycle, ACM Transactions on Algorithms 4 (2008).

[3] F. V. Fomin, D. Lokshtanov, F. Panolan, S. Saurabh, Representative sets of product families, in: ESA, 2014, pp. 443–454.

[4] H. Shachnai, M. Zehavi, Representative families: a unified tradeoff-based approach, in: ESA, 2014, pp. 786–797.

[5] R. Williams, Finding paths of length k in $O^*(2^k)$ time, Inf. Process. Lett. 109 (2009) 315–318.

[6] M. Zehavi, Mixing color coding-related techniques, in: ESA, 2015.

[7] M. Naor, J. L. Schulman, A. Srinivasan, Splitters and near-optimal derandomization, in: FOCS, 1995, pp. 182–191.

[3] By iteratively removing edges from G, it is easy to see that one can use ALG not only to determine whether G contains a simple path on exactly ℓ vertices from v to u, but also to return such a path. In this manner, even if $X = rand$, LCDAlg can be modified to accept only if (G, k) is a yes-instance.